

SAFETY

Spill Prevention and Secondary Containment Products

Workplace safety and environmental protection are challenges faced by Today's businesses. Safe handling, storing and transportation of materials must be carefully planned and implemented to prevent accidents and wastage without compromising on cost and productivity. Our range of spill prevention and secondary containment products seeks to do just that.



E5253
AN00680



E5102
AN00681



E5400
AN00682



E5469
AN00683

Code	Model	Loading Bearing Capacity UDL (kg)	Sump Capacity (litre)	Weight (kg)	Dimension (LxWxH) (cm)	Material
AN00680	E5253	900	220.4	28.35	136 x 74 x 43	100% Polythelyne
AN00681	E5102	1350	250.8	36	249 x 64 x 30	
AN00682	E5400	2700	250.8	41	137 x 137 x 30	
AN00683	E5469	3628.7	1457.4	132.44	182.88 x 203.2 x 73.66	

The above products are EPA 40 CFR 264. 175 (US Environmental Protection Agency).

Multi Workstation



Multi-purpose Racker/Stacker



E6004
AN00693

- Save space
- Accidents are reduced and exposure to hazardous material reduced
- Can reclaim spilled materials
- Holds up to two 205 litre drums
- Stackable design lets you stack up to four drums
- Load Bearing Capacity UDL (kg): 1,080
- Dimensions (cm): 123 x 104 x 51
- Weight (kg): 39.15

Multi-purpose Work Ramp



E5111
AN00699

- Easy loading
- Simply hooks onto Workstation to make loading easier
- Dimension: 65 cm x 122 cm x 16 cm
- Weight: 13.5kg
- Load Bearing Capacity UDL: 450kg

Link-Lock™



E5112
AN00698

- Combines multiple workstations to improve floor space efficiency
- 100% polyethylene - won't rust or corrode
- Sold in pairs
- Dimension: 24 cm x 18 cm x 9 cm
- Weight: 0.68 kg

2 Drum Workstation



E5117
AN00694

Dimension: 135 cm x 72 cm x 15 cm
Weight: 13.5 kg

4 Drum Workstation



E5116
AN00695

Dimension: 133 cm x 135 cm x 15 cm
Weight: 32.85 kg

6 Drum Workstation



E5115
AN00696

Dimension: 94 cm x 135 cm x 15 cm
Weight: 47 kg

8 Drum Workstation



E5110
AN00697

Dimension: 254 cm x 135 cm x 15 cm
Weight: 62.55 kg

Allinton Engineering & Trading Pte Ltd

Head Office: Block 803, King George's Avenue #01-234 Singapore 200803. Tel: 6296 0679 (10 lines) 6292 7728 Fax: 6297 0024

Branch Office: 21 Tuas Basin Link Singapore 638782 Tel: 6265 1888 (10 lines) Fax: 6265 5623

Web-site: <http://www.allinton.com.sg> E-mail: allinton@singnet.com.sg



SAFETY

Mobile Drum Dispenser (MDD)

E5300
AN00686



- Dimensions (cm) 175 L x 82 W x 67
- Weight (kg) 41.4
- Load Bearing Capacity UDL (kg) 270
- Sump cap. (litre) 304
- Light weight
- Tough polyethylene construction withstanding daily bumps and scuffs
- No rust or corrosion
- Integrally molded handles for extra strength with rolled grip to make lifting easy

3 Easy-Handling-Steps



Drum Scooter



E5205
AN00684

- Fits all drums up to 205 litres
- Load bearing capacity 225kg UDL
- 41.8 litre sump capacity
- Dimensions (cm): 88 x 23
- Weight (kg): 10.12

Poly-Overpack 95 Salvage Drum



E1237
AN00689

- Ideal for hazardous drum transport and storage
- Moulded for easy grip and pick-up
- 100% UV protected polyethylene
- Handling capacity: 292.5 kg
- Sump capacity: 361 litres
- Regulations: UN 1 H2/X295/S,
• UN H2T/Y295/S & DOT 49 CFR 173.3(c)

Free Standing Hand Operated Shower & Hand/Foot Operated Eyewash

Portable Emergency Shower/Face/Eye/Wash

- Soft cleansing action
- Produce soft streams of aerated water to quickly cleanse contaminants
- Stainless steel construction withstands external locations



EC090
AN00653

EC270
AN00657



Inlet Connection:
15 mm (1/2") BSP
Min. Water Supply Line:
DN25 (1") Normal Size
Min. Working Pressure:
15 mm (1/2") Aerated Outlet; 75 kpa
(10.7psi) Dynamic
10 mm (3/8") Aerated Outlet; 40 kpa
(5.7psi) Dynamic
Min. Flow Rate:
15 mm (1/2") Aerated Outlets 112 lpm
(24.8gpm)
10mm (3/8") Aerated Outlet 111 lpm
(24.6gpm)
Low Pressure Model:
10 mm (3/8") Aerated Outlet 20 lpm
(4.4gpm)
Waste Connection:
DN40 mm (1-1/2")
Mounting:
Floor Flange 150 mm (5.9")
Square; 4 Bolt Holes 11.11 mm (4.33")
at 100 mm (3.94") Centres

Emergency Eye/Face Wash



- Soft cleansing action
- Produce soft streams of aerated water to quickly cleanse contaminants
- Stainless steel construction withstands external locations

Inlet Connection:
15 mm (1/2") BSP
Min. Water Supply Line:
DN15 (1/2") Normal Size
Min. Working Pressure:
15 mm (1/2") Aerated Outlets: 180 kpa
(25.7psi) Dynamic
Low Pressure Model:
10 mm (3/8") Aerated Outlets: 80 kpa
(11.4 psi) Dynamic
Min. Flow Rate:
15 mm (1/2") Aerated Outlets 23 lpm
(5.1 gpm)
Low Pressure Model:
10 mm (3/8") Aerated Outlets 20 lpm
(4.4gpm)
Waste Connection:
DN40 mm (1/2") Normal Size
Mounting:
Floor Flange, 150 mm (5.9")
Square; 4 Bolt Holes 11.11 mm (4.33") at
100 mm (3.94") Centres



EF390
AN00667

Portable Emergency Eye Wash



FEN200
AN00715

Porta Stream II™ is a 15 minutes self-contained, gravity-fed eyewash station - SEI certified to meet ANSI Z 358.1 1998 Requirements.

- Eyewash station
- Eyesaline® concentrate solution
- Emergency eyewash sign
- Hanging bracket & Inspection Tag
- Instruction booklet

Pressurised Eye Wash/Body Spray 45L



- Rechargeable, soft spray controlled
- Stainless steel tank, stay-open ball valve & hand actuator
- Chrome plated eyewash outlet
- Hand held body spray with stainless steel braided hose

EL481
AN00678

Allinton Engineering & Trading Pte Ltd

Head Office: Block 803, King George's Avenue #01-234 Singapore 200803. Tel: 6296 0679 (10 lines) 6292 7728 Fax: 6297 0024

Branch Office: 21 Tuas Basin Link Singapore 638782 Tel: 6265 1888 (10 lines) Fax: 6265 5623

Web-site: <http://www.allinton.com.sg> E-mail: allinton@singnet.com.sg

