

HYDRAULIC

Cable Puller: 8000 lb. (35.8 kN) rated



Specifications

Weight	86lbs. (39kg)
Dimensions	Length: 11.5" Width: 26" (660.4mm) Height: 8.5" (215.9mm)
Drive Motor	1-1/2 Horsepower
Power Source 6800, 01, 02 and 05	120V 20A
Power Source 6800-22, 6802-22 and 6805-22	220VAC 50Hz
Pulling Force	Maximum-8000lbs. (35.8kN) Continuous-6500lbs. (28.9kN)
Pulling Speed-Feet (Meters) Per Minute	No Load: 9fpm, At 2000lbs. (8.8kN):8fpm, At 4000lbs. (17.9kN):7.5fpm, At 6000lbs. (26.7kN): 7fpm, At 8000lbs. (35.8kN):6fpm
Power Source	120V 20A
Rope-Average Breaking Strength or More	7/8 diameter (22.2mm); Double-Braided Polyester Composite - Rated at 3200lbs. (142kN)

Nothing Pulls Like The ULTRA Tugger™

- * Pull up to 8000 lbs.
- * Versi-Boom™ System allows you to make versatile and fast set-ups and pull 10' or 20' of extra cable easily.
- * Uses standard 3" rigid steel conduit for boom.
- * Direct gear drive.
- * Lightweight.
- * Portable.
- * Optional deluxe force gauge.

Cat. / UPC No.	Description	6800	6801	6802	6805
08000	Ultra Tugger™	✓	✓	✓	✓
01069	Force Gauge			✓	✓
00862	Pipe Adapter Sheave				✓
00863	Elbow Unit			✓	✓
00864	Nose Unit	✓		✓	✓
00865	Floor Mount		✓		
00866	Chain Mount			✓	✓
00867	"T" Stand				✓
00870	Wheeled Carriage			✓	✓
00871	Boom Mount			✓	✓
00835	3' Boom Tube			✓	✓
00791	4' Boom Tube			✓	✓
00811	3" Slip-in Coupling			✓	✓
00815	3-1/2" Slip-in Coupling			✓	✓
00820	4" Slip-in Coupling			✓	✓
00799	Adapter for Screw-on Coupling				✓
00782	3" Screw-on Coupling				✓
00783	3-1/2" Screw-on Coupling				✓
00784	4" Screw-on Coupling				✓
34136	7/8" x 300' (22.2mm x 91m) Rope				
34137	7/8" x 600' (22.2mm x 182m) Rope				
654/34362	Rope Stand			✓	✓
3048/23362	Storage Box			✓	✓
603/23405	Casters-2 Rigid, 2 Swivel				



AQ06800 / 00985
Floor Mount Package




AQ06801 / 00986
Conduit or Pole Mount Package



AQ06802 / 00987
Basic Package without rope




AQ06805 / 00993
Deluxe package with wheeled carriage without rope




Ultra Tugger™ With Force Gauge




Nose Unit



Wheeled Carriage



Pipe Adapter Sheave



Floor Mount



Boom Mount



Slip-in Coupling



Chain Mount



3' Boom



Adapter Screw-on



Elbow Unit



"T" Stand



4' Boom



Screw-on Coupling

Code No.	Model No.	Description
AQ06800	00985	Ultra Tugger™ Cable Puller with Standard Force Gauge, and Floor Mount.
AQ6800-22	00987	Same as 6800 except 220VAC 50Hz.

Allinton Engineering & Trading Pte Ltd

Head Office: Block 803, King George's Avenue #01-234 Singapore 200803. Tel: 6296 0679 (10 lines) 6292 7728 Fax: 6297 0024

Branch Office: 21 Tuas Basin Link Singapore 638782 Tel: 6265 1888 (10 lines) Fax: 6265 5623

Web-site: <http://www.allinton.com.sg> E-mail: allinton@singnet.com.sg



HYDRAULIC

Cable Puller: 6500 lb. (28.9 kN) rated



AQ06001


- * Pull up to 6,500 lbs. (28.9 kN) with less than 27 lbs. (120 N) of operator effort.
- * Unique floor mounting attachment for quick, reliable setup.
- * Leaf type mounting chains won't twist when tightening.
- * Heat treated steel serrated gripper feet for secure mounting to conduit.
- * Force Gauge included to constantly monitor the pull.
- * Right angle sheave allows the operator to stand out of the direct line of force.
- * Audio alarm high force warning and circuit breaker shut off at maximum force for added safety.
- * Tapered capstan and patented rope guidance system for better control of the rope when feeding onto the capstan.
- * Patented.

Specifications

Pulling Force	Maximum: 6,500lbs. (28.9kN)	Continuous: 4,500lbs. (20kN)
Dimensions:	Length: 20-3/4" (527mm) Height: 12" (305mm)	Width: 22-1/2" (572mm)
Weight:	6001, 6001-22: 108lbs. (49kg) 6000, 6000-22: 550lbs. (250kg)	6003: 454lbs. (206kg) 6006, 6006-22: 612lbs. (278kg)
Pulling Speed: -Feet (Meters) Per Minute	No. Load: 16.5 (5) At 2000lbs.: (8.8kN) - 11 (3.4) At 6000lbs.: (26.7kN) - 6 (1.8)	At 4000lbs.: (17.9kN) - 7.5 (2.3)
Power:	1-1/2 HP (1.1kW): 120VAC	1-1/2 HP (1.1kW): 220VAC 50Hz
Rope - Average: Braking Strength or More	3/4" (19.1mm) Double-Braided Composite - Rated at 26,000lbs. (115.6kN)	


Model No.	Description
AQ6001 P/N: 29627	Super Tugger Cable Puller Power Unit. Includes force gauge and vise chains.
AQ6001-22 P/N: 31466	Same as 6001 except 220VAC 50Hz.
AQ6000 P/N: 29909	Super Tugger Complete Puller Package. Includes 6001 Super Tugger Cable puller power unit, pipe adapter sheave, flexible pipe adapter, 12" hook type cable, sheave, mobile extension boom, 2", 2-1/2", 3", 3-1/2", 4" extension bushings, 3/4" x 3'- (19.1mm x 91m) double-braided polyester rope, rope roll stand, floor mount and steel storage box with casters.

Key	Cat./ UPC No.	Description	6001/ 29627	6000/ 29909	6003/ 36241	6006/ 30435	6001-22/ 31466
6001 Cable Puller Parts							
	29631	Vise Chain Unit includes one each of the following five items below (Two complete Vise Chain sets are required)					
	35661	(1) Vise Chain	1				1
	29630	(2) Vise Chain Handle	1				1
	53965	(3) Vise Chain Retaining Screw	1				1
	35657	(4) Washer	1				1
	35660	(5) Chain Positioner	1				1
	37179	120VAC Force Gauge	1				
	35638	220VAC Force Gauge					1
Cable Pulling Components							
A	6001/ 29697	Cable Puller		1	1	1	
B	6049/ 29826	Pipe Adapter Sheave		1	1	1	
C	6085/ 29912	Flexible Pipe Adapter		1	1	1	
D	6080/ 29964	Mobile T-Boom		1	1	1	
D	16782	2" Extension Bushing		1	1	1	
D	16783	2-1/2" Extension Bushing		1	1	1	
D	16784	3" Extension Bushing		1	1	1	
D	16785	3-1/2" Extension Bushing		1	1	1	
D	16786	4" Extension Bushing		1	1	1	
E	3048/ 23362	Storage Box		1	1	1	
	695/ 30239	Casters		1	1	1	
F	6037/ 35605	Cable Puller Floor Mount		1	1	1	
G	35098	3/4" x 300' (19.1mm x 91m) Double-Braided Composite Rope		1			
G	35100	3/4" x 600' (19.1mm x 182m) Double-Braided Composite Rope				1	
H	644/ 15316	Rope Stand		1			
	654/ 34362	Rope Stand				1	
J	8012/ 00872	12" (304.8mm) Hook Sheave		1		1	




P/N: 29909

6000 Super Tugger
Cable Pulling System



P/N: 36241

6003 Super Tugger
Cable Pulling System



P/N: 30435

6006 Super Tugger
Cable Pulling System

Allinton Engineering & Trading Pte Ltd

Head Office: Block 803, King George's Avenue #01-234 Singapore 200803. Tel: 6296 0679 (10 lines) 6292 7728 Fax: 6297 0024

Branch Office: 21 Tuas Basin Link Singapore 638782 Tel: 6265 1888 (10 lines) Fax: 6265 5623

Web-site: <http://www.allinton.com.sg> E-mail: allinton@singnet.com.sg

