

HYDRAULIC

Double-Braided Composite Rope for high force cable pullers



AQ35098

- * Custom made to Greenlee specifications to provide 4:1 Safety Factor required for cable pulling.
- * Double-braided inner core with an extra double-braided outer jacket for added strength and less stretch; White with green tracer.
- * Rot and mildew resistant.
- * Factory spliced eyes at both ends.
- * Lowest stretch.
- * Select a rope with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.



Rope Diameter	Rope Length		Code No.	Maximum Rated Capacity		Average Braking Strength		Weight		Rope Stand
								lbs.	kg	
For The 6001 Puller 3/4" (19.1mm)	300'	91m	AQ35098	6,500lbs.	28.9kN	26,000lbs.	115.6kN	58	26.3	644
	600'	182m	AQ35100	6,500lbs.	28.9kN	26,000lbs.	115.6kN	113	51.3	654
	1,200'	365m	AQ35101	6,500lbs.	28.9kN	26,000lbs.	115.6kN	230	104.3	t
For The 6800 Puller 7/8" (22.2mm)	300'	91m	AQ34136	8,000lbs.	35.6kN	32,000lbs.	142.3kN	90	40.8	654
	600'	182m	AQ34137	8,000lbs.	35.6kN	32,000lbs.	142.3kN	178	80.7	654
	1,200'	365m	AQ34138	8,000lbs.	35.6kN	32,000lbs.	142.3kN	359	163.3	t

t This rope does not fit on a rope stand. Use reel jacks and a spindle to dispense.

Cable Gel™ Cable Pulling Lubricant



AQ35098

- * Polymer based lubricant offers lower friction and easier pulling.
- * Compatible with all cable insulation types.
- * Cleans up quickly. Non-staining.
- * Higher lubricity than competitive products.
- * Will not cement itself to the pipe.
- * Dries slowly.
- * Can be applied by hand or pump.
- * Will not breakdown or separate after exposure to heat or cold.
- * Environmentally safe / non-hazardous.

Code No.	Model No.	Description	P/N:
GEL-Q	AQ35211	Cable-Gel™ One Quart Squeeze Bottle (.95L)	35207
GEL-1	AQ35212	Cable-Gel™ One Quart (3.79L)	35208
GEL-5	AQ35213	Cable-Gel™ 5 Gallon (18.93L)	35209
GEL-55	AQ35214	Cable-Gel™ 55 Gallon (208.18L)	35210

Hook Sheaves for any cable puller



AQ55872

- For use with any Greenlee cable puller.
- Strong, welded steel frames.
- Forged steel closure type hooks with 1" (25.4 mm) opening.
- All three sheaves are aluminum alloy with self-lubricating bearings.

Sheave Diameter	AQ55872	AQ55873	AQ55874
Description	12" (304.8mm)	18" (457.2mm)	24" (609.6mm)
	Code No.	Code No.	Code
Roll Pin	AQ50700	AQ50700	AQ50700
Sheave Pin	AQ00838	AQ00846	AQ00850
Sheave Pin Clip	AQ50302	AQ50302	AQ50302
Sheave Unit	AQ00843	AQ00844	AQ00845
Yoke Frame	AQ00854	AQ00855	AQ00856

Code No.	P/N:	Outside Diameter	Inside Radius	Width	Weight	Maximum Rated Capacity
AQ55872	00872	12" (304.8mm)	3-7/8" (98.4mm)	5" (127mm)	28lbs (12.7kg)	8,000lbs. (35.8kN)
AQ55873	00873	18" (457.2mm)	7" (177.8mm)	6" (152.4mm)	44lbs (19.9kg)	8,000lbs. (35.8kN)
AQ55874	00874	24" (609.6mm)	9-7/8" (250.8mm)	6-1/2" (165.1mm)	67lbs (30.3kg)	8,000lbs. (35.8kN)

Allinton Engineering & Trading Pte Ltd

Head Office: Block 803, King George's Avenue #01-234 Singapore 200803. Tel: 6296 0679 (10 lines) 6292 7728 Fax: 6297 0024

Branch Office: 21 Tuas Basin Link Singapore 638782 Tel: 6265 1888 (10 lines) Fax: 6265 5623

Web-site: <http://www.allinton.com.sg> E-mail: allinton@singnet.com.sg

