

WELDING PRODUCTS

Dark Glass

2" x 4"

AS00228 No 10
AS00342 No 11
AS00343 No 12
AS00344 No 13



Clear Glass

2" x 4" AS00229



Nozzle Cleaner



AS00226

Nozzle Cleaner (Box Type)



AS00227

Cable Lux

| Code No. | Size |
|----------|--------|
| AS00214 | 300AMP |
| AS00215 | 400AMP |
| AS00216 | 500AMP |



AS00214

Dalo Marker



AS00237

| Code No. | Colour |
|----------|--------|
| AS00237 | White |
| AS00238 | Yellow |

Nissan Marker



AS00239

| Code No. | Colour |
|----------|--------|
| AS00239 | White |
| AS00240 | Yellow |

Slate Pencil



AS00232

Chalk



AS00233

| Code No. | Colour |
|----------|--------|
| AS00233 | Yellow |
| AS00234 | White |
| AS00235 | Red |
| AS00236 | Blue |

Crayon



AS00241

| Code No. | Colour |
|----------|--------|
| AS00241 | White |
| AS00242 | Yellow |
| AS00243 | Red |
| AS00244 | Blue |

Solid Marker



AS00245

| Code No. | Colour |
|----------|--------|
| AS00245 | Yellow |
| AS00246 | White |

Tempilstiks

Tempilstiks are made of materials with melting points calibrated to a guaranteed tolerance of $\pm 1\%$. There are a total of 103 temperature ratings with melting points systematically spaced between 100°F/38°C and 2500°F/1371°C. Most can be certified to be lead and sulfur free. Every Tempilstik is traceable by lot number to the specific batch of raw material from which it was made.

AS00247



Tempilstik, Tempilaq and Tempil Pellets are available in the following temperatures:

| °F | °C | °F | °C | °F | °C | °F | °C | °F | °C | °F | °C |
|-----|----|-----|-----|-----|-----|------|-----|------|------|------|------|
| 100 | 38 | 206 | 97 | 325 | 163 | 575 | 302 | 1300 | 704 | 2150 | 1177 |
| 103 | 39 | 213 | 101 | 331 | 166 | 600 | 316 | 1350 | 732 | 2200 | 1204 |
| 106 | 41 | 219 | 104 | 338 | 170 | 625 | 329 | 1400 | 760 | 2250 | 1232 |
| 109 | 43 | 225 | 107 | 344 | 173 | 650 | 343 | 1425 | 774 | 2300 | 1260 |
| 113 | 45 | 231 | 111 | 350 | 177 | 700 | 371 | 1450 | 788 | 2350 | 1288 |
| 119 | 48 | 238 | 114 | 363 | 184 | 750 | 399 | 1480 | 804 | 2400 | 1316 |
| 125 | 52 | 244 | 118 | 375 | 191 | 800 | 427 | 1500 | 816 | 2450 | 1343 |
| 131 | 55 | 250 | 121 | 388 | 198 | 850 | 454 | 1550 | 843 | 2500 | 1371 |
| 138 | 59 | 256 | 124 | 400 | 204 | 900 | 482 | 1600 | 871 | | |
| 144 | 62 | 263 | 128 | 413 | 212 | 932 | 500 | 1650 | 899 | | |
| 150 | 66 | 269 | 132 | 425 | 218 | 950 | 510 | 1700 | 927 | | |
| 156 | 69 | 275 | 135 | 438 | 226 | 977 | 525 | 1750 | 954 | | |
| 163 | 73 | 282 | 139 | 450 | 232 | 1000 | 538 | 1800 | 982 | | |
| 169 | 76 | 288 | 142 | 463 | 239 | 1022 | 550 | 1850 | 1010 | | |
| 175 | 79 | 294 | 146 | 475 | 246 | 1050 | 566 | 1900 | 1038 | | |
| 182 | 83 | 300 | 149 | 488 | 253 | 1100 | 593 | 1950 | 1066 | | |
| 188 | 87 | 306 | 152 | 500 | 260 | 1150 | 621 | 2000 | 1093 | | |
| 194 | 90 | 313 | 156 | 525 | 274 | 1200 | 649 | 2050 | 1121 | | |
| 200 | 93 | 319 | 159 | 550 | 288 | 1250 | 677 | 2100 | 1149 | | |

*Series "R" tempil Pellets available in these temperatures, 550°F and below. Regular Pellets can be used for reducing atmosphere. Aerosol Tempilaq not available below 150°F/66°C.

Fibreglass Tape



Size 2" x 3mm x 30m

AS00374

Fibreglass Cloth

| | |
|-----------------------|----------------------|
| Model No. | TX3000 |
| Code No. | AS00250 |
| Density | 1600g/m ² |
| Temperature | 550°C |
| Resistance Capability | (Max Continuously) |
| Weave Type | Plain |
| Colour | White |
| Finish | Texturised |
| Thickness | 3.0mm |
| Width | 1.0m |
| Roll Length | 15m |



Fibreglass Cloth

| | | |
|-----------------------|----------------------|----------------------|
| Model No. | HT800 | G1700 |
| Code No. | AS00248 | AS00249 |
| Density | 1650g/m ² | 1100g/m ² |
| Temperature | 550°C | 550°C |
| Resistance Capability | (Max Continuously) | (Max Continuously) |
| Weave Type | Satin | Plain |
| Colour | Golden Brown | Golden Brown |
| Finish | Heat Treated | Texturised |
| Thickness | 1.0mm | 1.7mm |
| Width | 1.0m | 1.0m |
| Roll Length | 50m | 30m |



Allinton Engineering & Trading Pte Ltd

Head Office: Block 803, King George's Avenue #01-234 Singapore 200803. Tel: 6296 0679 (10 lines) 6292 7728 Fax: 6297 0024

Branch Office: 21 Tuas Basin Link Singapore 638782 Tel: 6265 1888 (10 lines) Fax: 6265 5623

Web-site: <http://www.allinton.com.sg> E-mail: allinton@singnet.com.sg

WELDMASTER®